


- | | | | |
|---|---|--|--|
| R89-1NCBG Finish(BG) <input type="checkbox"/> | R89-1NCC Finish(C) <input type="checkbox"/> | LG89-7NCC Finish(C) <input type="checkbox"/> | LG89-8NCC Finish(C) <input type="checkbox"/> |
| R89-1NCB Finish(B) <input type="checkbox"/> | R89-1NCK Finish(K) <input type="checkbox"/> | LG89-7NCK Finish(K) <input type="checkbox"/> | LG89-8NCK Finish(K) <input type="checkbox"/> |



Specifications

Features

- 1.75 GPM Flow Rate (Showerhead)
- PVD Finish (K Finish Only)
- Raincan Showerhead
- Temperature Control Only
- Secure Pfit™ with Anti Handle Wobble
- Quick Connect Tub Spout (8NC Only)
- Removable Quick Connect for 1/2" IP Option (8NC Only)
- Tub & Shower Trim (8NC)
- Shower Only Trim (7NC)
- Valve Trim Only (1NC)
- Requires OX8/JX8 Valve (Sold Separately)
- Limited Lifetime Warranty

Code Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes:

- IAPMO Certified to ASME A112.18.1/CSA B125.1
- CEC Certified/CALGreen compliant
- EPA WaterSense Certified
- ADA Compliant - ANSI A117.1 (Lever Handle Only)



Dimensions

