

Highlights

- Complete Collection with Coordinating Roman Tub and Tub & Shower Options
- ¼ Turn Ceramic Disc Valves
- Pforever Warranty®

Code Compliance

Price Pfister products are designed and manufactured in compliance with the following standards and codes:

- IAPMO certified • ASME A112.18.1
- CSA B125 certified • ANSI A117.1 (Lever handles only)

48 Series

SANTIAGO™

4" Centerset Lavatory Faucet


Lever Handles

3-Hole Installation

1/4 Turn Ceramic Disc Valves

Finishes	T48-ST0C	T48-ST0K	T48-ST0Y
Tuscan Bronze			X
Polished Chrome	X		
Satin Nickel		X	

Features	T48-ST0C	T48-ST0K	T48-ST0Y
Metal Lever Handles	X	X	X
3-Hole Installation	X	X	X
ADA Approved	X	X	X
Metal Pop-Up	X	X	X
High Arc Spout	X	X	X
¼ Turn Ceramic Disc Valves	X	X	X
Step-By-Step Installation Instructions	X	X	X
Pforever Warranty®	X	X	X



- T48-ST0C
- T48-ST0K
- T48-ST0Y

For additional information, please contact your Price Pfister representative, or visit our website at www.pricepfister.com.

Project: _____

Contractor: _____

SS-048-11

1-800-PFAUCET www.pricepfister.com
 19701 DaVinci, Lake Forest, CA 92610
 06/13/07

Price Pfister®
 Pfreshest Ideas in Pfaucets


INSTALLATION DIMENSIONS

48 Series

SANTIAGO™

4" Centerset Lavatory Faucet

Critical Dimensions:	
Minimum Hole Size	1 - 1 1/2 Dia Thru Hole 3 Places
Valve Centerline to Back Splash	2 5/16 Min



CAUTION:
When using the compression fittings in this package, with these types of installations, the installer must flare or bead the water supply lines to avoid blow-out conditions. Avoiding such steps in the installation of the unit may result in water damage.

Connect inlet supply lines by assembling brass supply nut (A), friction ring (B) and cone washer (C) onto 3/8" O.D. straight copper tube. Bead or flare. Wrench tighten.

Dimensions are in Inches

1-800-PFAUCET www.pricepfinder.com
19701 DaVinci, Lake Forest, CA 92610
06/14/07