

**Highlights**

- ¼ Turn Ceramic Disc Valves
- Pforever Warranty®
- Step-By-Step Installation Instructions

**Code Compliance**

Price Pfister products are designed and manufactured in compliance with the following standards and codes:

- IAPMO certified
- ASME A112.18.1
- CSA B125 certified
- ANSI A117.1 (Lever handles only)

**48 Series**

*Bristol*<sup>™</sup>

**4" Centerset Lavatory Faucet**

Lever Handles

3-Hole Installation

1/4 Turn Ceramic Disc Valves

<b>Finishes</b>	048CT0C	048CT0K
Polished Chrome	x	
Satin Nickel		x

<b>Features</b>	048CT0C	048CT0K
Metal Lever Handles	x	x
ADA Approved	x	x
¼ Turn Ceramic Disc Valves	x	x
Pforever Warranty®	x	x



048CT0C

048CT0K

For additional information, please contact your Price Pfister representative, or visit our website at [www.pricepfister.com](http://www.pricepfister.com).

**Project:** \_\_\_\_\_

**Contractor:** \_\_\_\_\_

SS-048-10

**1-800-PFAUCET** [www.pricepfister.com](http://www.pricepfister.com)  
 19701 DaVinci, Lake Forest, CA 92610  
 08/30/06

**Price Pfister**<sup>®</sup>  
 Pfreshest Ideas in Pfaucets.

# INSTALLATION DIMENSIONS


## 48 Series

# Bristol™


### 4" Centerset Lavatory Faucet

#### Critical Dimensions:

Minimum Hole Size	1 1/2 DIA Thru Hole 3 Places
Valve Centerline to Back Splash	2 11/32 Min



Dimensions are in Inches



**CAUTION:** When using the compression fittings in this package, with these types of installations, the installer must flare or bead the water supply lines to avoid blow-out conditions. Avoiding such steps in the installation of the unit may result in water damage.

Connect inlet supply lines by assembling brass supply nut (A), friction ring (B) and cone washer (C) onto 3/8" O.D. straight copper tube. Bead or flare. Wrench tighten.

**1-800-PFAUCET** [www.pricepfister.com](http://www.pricepfister.com)  
 19701 DaVinci, Lake Forest, CA 92610  
 08/30/06

Price Pfister®

Pfreshest Ideas in Pfaucets.