


Highbury™ Pull-Down Kitchen Faucet

- LG529-HGC Finish(C) ☐
- LG529-HGS Finish(S) ☐
- LG529-HGY Finish(Y) ☐



Specifications

Features

- 1.8 GPM Flow Rate
- 1-Hole Installation
- 3 Function Pull-Down Sprayer (Stream, Spray, and HydroBlade™)
- 13.5" Extended Hose Length
- Nylon Braided Hose
- 360° Rotating High Arc Spout
- AccuDock™ Sprayhead Docking
- Forward Handle Operation
- Pfaster Connect™
- Optional Soap Pump Available, Order KSD-SRD* Separately
- Optional Deckplate Available, Order 961-221* Separately
- Convert to LEED Requirements with Separate Insert: Low Flow Regulator 1.5 GPM (941-683) and 1.0 GPM (941-444)
- Pforever Seal™ Ceramic Disc Valve
- Limited Lifetime Warranty




Code Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes:

- IAPMO Certified to ASME A112.18.1/CSA B125.1 including:
 - ASME A112.18.3 (Backflow Prevention)
- NSF/ANSI/CAN61:Q≤1
- CEC Certified/CALGreen compliant
- ADA Compliant - ANSI A117.1 (Lever Handle Only)



Dimensions



Ø1-3/8 Min to Ø1-1/2 Max. Deck Hole Openings