


Single Control Kitchen Faucet

- | | |
|--|--|
| LG34-1PCO Finish(C) <input type="checkbox"/> | LG34-4PCO Finish(C) <input type="checkbox"/> |
| LG34-1PSO Finish(S) <input type="checkbox"/> | LG34-4PSO Finish(S) <input type="checkbox"/> |
| LG34-1PYO Finish(Y) <input type="checkbox"/> | LG34-4PYO Finish(Y) <input type="checkbox"/> |
| LG34-3PCO Finish(C) <input type="checkbox"/> | |
| LG34-3PSO Finish(S) <input type="checkbox"/> | |
| LG34-3PYO Finish(Y) <input type="checkbox"/> | |



- 1, 2, 3 or 4-Hole Installation
- Pforever Seal™

Specifications

Features

- 1.8 GPM Flow Rate
- 360° Rotating Spout
- 1, 2, 3 or 4-Hole Installation; Includes Both Deck Plate and Single Post Mounting Ring
- Optional Deckplate (Excludes 3P)
- Includes Matching Side Spray (Excludes 1P)
- Mounting Hardware Included
- Mounting Posts Included
- Pforever Seal™ Ceramic Disc Valve
- Limited Lifetime Warranty


Code Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes:

- IAPMO Certified to ASME A112.18.1/CSA B125.1 including:
 - ASME A112.18.3 (Backflow Prevention)
- NSF/ANSI/CAN61:Q≤1
- CEC Certified/CALGreen compliant
- ADA Compliant - ANSI A117.1 (Lever Handles Only)



Dimensions



Ø1-3/8 Min to Ø1-1/2 Max. Deck Hole Openings