


*F529-7SLC Finish(C) ☐

*F529-7SLMC Finish(MC) ☐

F529-7SLS Finish(S) ☐

*International Only



Specifications

Features

- 1.8 GPM Flow Rate
- 1.5 GPM Flow Rate with Insert 941-055
- 1, 2, 3, or 4-Hole Installation; Deck Plate or Single Hole Mounting Option
- 2 Function Pull-Down Sprayer
- 60" Nylon Hose
- AccuDock™ Spray Head Docking
- Concealed Screw

- 360° Rotating Spout
- Flex-Line Supply Lines
- High Arc Spout
- Mounting Hardware Included
- PVD Finish
- TiteSeal™ Technology
- Soap Dispenser Included
- Quick Install Tool
- Pfaster Connect™
- Pforever Seal™ Ceramic Disc Valve
- Limited Lifetime Warranty




Code Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes:

- IAPMO Certified to ASME A112.18.1/CSA B125.1 including:
 - ASME A112.18.3 (Backflow Prevention)
- NSF/ANSI/CAN61:Q≤1
- CEC Certified/CALGreen compliant
- ADA Compliant - ANSI A117.1 (Lever Handle Only)




Dimensions




Ø1-3/8 Min to Ø1-1/2 Max. Deck Hole Openings

Optional Included Deckplate



Top Filling Soap Dispenser



36 Inch Supply Lines with 3/8 Female Compression Brass Connections

