


## Venturi™ Pull-Down Kitchen Faucet

- F-529-7VNB Finish(B) ☐  
 \*F-529-7VNC Finish(C) ☐  
 F-529-7VNGS Finish(GS) ☐  
 \*International Only



## Specifications

### Features

- 1.8 GPM Flow Rate
- Unique Ribbon Water Flow Pattern
- Spot Defense Finish which Resists Spots and Fingerprints (GS Finish Only)
- 1, 2, 3, or 4-Hole Installation; Deck Plate or Single Hole Mounting Option
- 2 Function Pull-Down Sprayer
- AccuDock™ Sprayhead Docking
- Mounting Hardware Included
- Nylon Flex-Line Supply Lines
- 360° Rotating Spout
- Forward Handle Operation
- Pfister Connect™
- PVD Finish(GS Finish Only)
- Soap Dispenser
- Quick Install Tool
- TiteSeal™ Deckplate
- Pforever Seal™ Ceramic Disc Valve
- Limited Lifetime Warranty




### Code Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes:


- IAPMO Certified to ASME A112.18.1/CSA B125.1 including:
  - ASME A112.18.3 (Backflow Prevention)
- NSF/ANSI/CAN61:Q≤1
- CEC Certified/CALGreen compliant
- ADA Compliant - ANSI A117.1 (Lever Handle Only)




## Dimensions



### Optional Included Deckplate



### Top Filling Soap Dispenser



36 Inch Supply Lines with  
3/8 Female Compression  
Brass Connections

